

Flexoper Sanded

5mm thick reinforced SBS modified bituminous membrane

| | Component/Ingredients | % | |
|----|---------------------------|----------|--|
| 1. | Petroleum Asphalt | 75 – 82% | |
| 2. | Styrene Butadiene Styrene | 16-22% | |
| 3. | Talcum or granules | 2-25% | |
| 4. | Glass matting | 0-5% | |

FORMULA / MIXTURE

Exposure Standard For Pure Components, TLV in air averaged over an 8-hour daily exposure (ACGHI 1987-88)

| | |
|---------------------|---------------------------------------|
| 5mg/m ³ | Petroleum Asphalt (For Fumes or Mist) |
| Not Established | Styrene Butadiene Styrene |
| 15mg/m ³ | Sand (For Respirable Dust) |

Physical Data:

| | |
|---------------------------------------|---|
| Initial Boiling Point, of | 700 |
| Specific Gravity (H ² O=1) | 1.01-1.06 |
| Vapour Pressure (MMHg) | NA |
| Percent Volatile (by volume %) | NA |
| Vapour Density (AIR=1) | NA |
| Evaporation Rate (n-Butyl Acetate=1) | NA |
| Solubility in Water | Nil |
| Appearance and Odour | Petroleum odour increases with temperature. Seem-solid at application temperatures. May contain Hydrogen Sulphide, a toxic gas. |

Fire and Explosion Hazard Data:

| | |
|-----------------------|--|
| Flash Point – COC, oF | Above 450 |
| Flammable Limits LEL | NDA |
| UEL | NDA |
| Extinguishing Media | Foam, Water Fog, Dry Chemical, CO ² |

Special Fire Fighting Procedures:

Do not enter confined fire space without proper protective equipment including self-contained breathing apparatus. See hazardous decomposition products.

Reactivity Data:

| | |
|--------------------------------------|---------------------------------|
| Stability (Thermal, Light) | Stable |
| Incompatibility (Materials to avoid) | May react with strong oxidisers |

Hazardous Decomposition Products:

Thermal decomposition products are highly dependent on the combustion conditions. A complex of airborne solid, liquid, particulates and gases will evolve when this material undergoes pyrolysis or combustion. Carbon monoxide and other unidentified organic and inorganic compounds may be formed upon combustion.

| | |
|----------------------------------|----------------|
| Hazardous Decomposition Products | Will not occur |
|----------------------------------|----------------|

Spill or leak procedures:

| | |
|------------------------|---|
| Steps in case of spill | Recover by placing in suitable container. |
| Waste disposal method | Observe federal, state and local regulations covering non-hazardous solid waste disposal. |

Emergency, First Aid and Special Protection Information:

| | |
|------------------------|---|
| Eyes | Avoid eye contact, irrigate with plenty of water, see a physician. Use splash goggles or face shield when eye contact may occur. |
| Skin | If splashed on skin, cool water. Do not use solvents or thinners to remove material from skin. Get immediate medical attention. |
| Inhalation | Fumes from hot material from skin. Get immediate medical attention. |
| Respiratory Protection | If conditions create airborne concentrations which exceed an exposure standard, the use of an approved respirator or air supplied breathing equipment is recommended. |

Ventilation

Use adequate ventilation to keep the airborne concentrations of the material below the exposure standard.

Health Hazard Data:

Eyes

The cool solid material is not expected to cause eye irritation. Thermal burns may result from contact with hot material.

Skin

The cool solid material is not expected to cause skin irritation. Thermal burns may result from contact with hot material.

Ingestion

Not expected to be acutely toxic by ingestion. If swallowed, do not induce vomiting; call a physician.

Effects of overexposure

Inhalation of high fume or mist concentrations may cause dizziness, headache or nausea.

Hazardous according to OSHA (1910.1200) or one or more state Right to Know lists.

Special Precautions:

Precautions to be taken in handling and storing: avoid skin contact with hot product.

Avoid breathing vapours. Do not heat above flash point.

Other precautions: Practice good hygiene, wash thoroughly after working with product and before eating or smoking. Remove contaminated clothing and launder before re-use.

Transportation:

DOT hazard classification: not regulated by DOT

| | HEALTH | FLAMMABILITY | REACTIVITY |
|-----------------|--------|--------------|------------|
| HMIS *) rating | 1 | 1 | 0 |
| NFPA **) rating | 1 | 1 | 0 |

NOTICE:

These ratings involve data and interpretations that may vary from company to company and are intended only for rapid, general identification of the magnitude of the specific hazard.

TO DEAL WITH ADEQUATELY WITH THE SAFE HANDLING OF THIS MATERIAL, ALL THE INFORMATION CONTAINED IN THIS M.S.D.S. MUST BE CONSIDERED.

The customer is responsible for determining the proper personal protective equipment needed for its particular use of this material.

*) Hazardous Materials Identification Systems (HMIS) Revised RWA Materials Rating Manual, National Paint & Coatings Association, fall 1984.

***) NFPA 704 Standard System for the Identification of the Fire Hazards of Materials, National Fire Protection Association, 1985.

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must make assure proper use and disposal of these materials and the safety and health of employees and customers.

Information on this form is furnished solely for the purpose of compliance with OSHA Hazard Communication Standard, 20 CFR 1910.1200, the Workplace Hazardous Material Information System (WHMIS), and shall not be used for any other purpose.

Date revised June 2014